

								
Product:	BAL grout	BAL wide joint	Superflex	Superflex wide joint	Microflex	Microflex wide joint	Micromax2	BAL Easy epoxy
Range Position:	Basic		Good		Better		Best	Specialist
<b>LOCATION</b>								
Interior (dry) Walls	✓	✗	✓	✗	✓	✗	✓	✓
Exterior Walls	✓	✗	✓	✗	✓	✗	✓	✓
Interior (dry) Floors	✗	✓	✗	✓	✗	✓	✓	✓
Exterior Floors	✗	✓	✗	✓	✗	✓	✓	✓
<b>ENVIRONMENTS</b>								
Walls: Intermittent wet*	✓	✗	✓	✗	✓	✗	✓	✓
Walls: Domestic shower	✓	✗	✓	✗	✓	✗	✓	✓
Walls: Power shower	✓*	✗	✓	✗	✓	✗	✓	✓
Walls: Communal shower	✓*	✗	✓	✗	✓	✗	✓	✓
Walls: Swimming pool	✓	✗	✓	✗	✓	✗	✗	✓
Walls: Minor vibration	✓*	✗	✓	✗	✓	✗	✓	✓
Walls: Limited deflection	✓*	✗	✓	✗	✓	✗	✓	✓
Floors: Intermittent wet*	✗	✓	✗	✓	✗	✓	✓	✓
Floors: Domestic shower	✗	✓	✗	✓	✗	✓	✓	✓
Floors: Power shower	✗	✓*	✗	✓	✗	✓	✓	✓
Floors: Communal shower	✗	✓*	✗	✓	✗	✓	✓	✓
Floors: Swimming pool	✗	✓	✗	✓	✗	✓	✗	✓
Floors: Floating wood	✗	✓*	✗	✗	✗	✗	✓	✓
Floors: Minor vibration / Heavy use	✗	✓*	✗	✓	✗	✓	✓	✓
Floors: Limited deflection	✗	✓*	✗	✓	✗	✓	✓	✓
<b>TILES</b>								
Ceramics	✓	✓	✓	✓	✓	✓	✓	✓
Porcelain	✓*	✓*	✓	✓	✓	✓	✓	✓
Glass	✓*	✗	✓	✗	✓	✗	✓	✓
Metalic glazed	✓*	✗	✓	✗	✓	✗	✓	✓
Marble, limestone, travertine	✓	✓	✓	✓	✓	✓	✓	✗
Granite, slate	✓*	✓*	✓	✓	✓	✓	✓	✗
<b>SPECIFIC FEATURES</b>								
Antibacterial	✗	✗	✗	✗	✓	✓	✓	✗
Moderate trafficking	✗	✓	✗	✓	✓	✓	✓	✓
Heavy trafficking	✗	✓*	✗	✓	✓	✓	✓	✓
Efflorescence-free	✗	✗	✗	✗	✗	✗	✓	✗
Setting time	24 hours	24 hours	24 hours	24 hours	24 hours	24 hours	2 - 3 hours	24 hours
Working time at 20°C	60 mins	30 mins	30 mins	30 mins	30 mins	30 mins	> 30 mins	> 30 mins
Minimum joint width	1mm	2mm	1mm	3mm	1mm	3mm	1mm	1mm
Maximum joint width	3mm	12mm	5mm	20mm	5mm	20mm	20mm	12mm
Wide colour range	✗	✗	✗	✗	✗	✗	✓	✗
Colour matched sealants	✗	✗	✗	✗	✗	✗	✓	✗

✓ = suitable for use  
 ✓\* = suitable when using GT1 admix  
 ✗ = not suitable for use