



BAL

silicone

Silicone Sealant



- Flexible: ready-to-use
- Mould-resistant
- Suitable for sinks/
worktops/baths/basins
- Service temperature range:
-50°C to +150°C

CREAM

silicone

Flexible waterproof ready-to-use silicone rubber sealant

USE FOR

General sealing, including movement joints in FLOOR and WALL tiling installations

For surfaces including:

- Acrylic
- Ceramic
- Fibreglass
- Glass
- Porcelain

INTERIOR and EXTERIOR walls

DRY and WET environments

Suitable for:

- Domestic/light commercial applications

NOT suitable for:

- Aquariums

IMPORTANT NOTE: This product must NOT be used on sensitive surfaces that could react with acetic acids released during cure.

KEY FEATURES

- Firm bonding

When fully cured:

- Good service temperature range (-50°C to +150°C)

COVERAGE

Varies according to size of bead.

This 310ml cartridge of **BAL SILICONE** typically provides:

- 8.8m for 6x6mm bead

SURFACE PREPARATION

Before sealing, ensure that all surfaces are clean, dry, free from dust, grease and any contaminants that may affect adhesion.

APPLICATION

1. Cut off tip of cartridge, leaving thread intact.
2. Screw on nozzle.
3. Cut nozzle to required width and angle.
4. Place cartridge in caulking gun and apply steady bead of silicone to required area.
5. Smooth silicone with wetted spatula or similar.

NOTE: Sealant skins in 5-10 minutes.

6. Allow to cure (approx. 24 hours per 4mm thickness).

TECHNICAL ADVISORY SERVICE

For free expert guidance on use of this product, or any aspect of tiling, contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE on Tel: 01782 591120 or 0845 600 1 222 or Fax: 01782 591121.

SHELF LIFE

12 months if stored in a dry place under normal dry frost-free conditions.

25 YEAR GUARANTEE

All BAL products are supplied with a 25 year product guarantee. Contact BAL Marketing Department for full details.

CONDITIONS OF SALE

Sold subject to the Company's Conditions of Sale. Available on request.

HEALTH & SAFETY WARNING

BAL SILICONE

Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection.

Building Adhesives Limited, Longton Road, Trentham, Stoke-on-Trent, England, ST4 8JB
Tel: +44 (0) 1782 591100

310ml

MANUFACTURED UNDER A QUALITY MANAGEMENT SYSTEM APPROVED BY BSI

BUILDING ADHESIVES LTD

Longton Road, Trentham
Stoke-on-Trent, ST4 8JB, England
www.bal-adhesives.com

Sales Tel: +44 (0) 1782 591160
Fax: +44 (0) 1782 591131

Technical Tel: +44 (0) 1782 591120 or
+44 (0) 845 600 1 222
Fax: +44 (0) 1782 591121

Unit 6 Plato Business Park, Damastown Industrial Est.
Damastown, Dublin 15, Ireland

Tel: +353 (0) 1 8222 776 Fax: +353 (0) 1 8222 777

